



## UniMac SoftMount Washer Extractor

### Model UX Series

Front Load Industrial Washing  
Machine Non-Coin Operated

Available Capacity: 15.9kg, 24.9kg,  
34kg, 45.4kg, 61.2kg, 74.8kg

#### FEATURES & PERFORMANCE : REDUCE LAUNDRY RUNNING COSTS

Understand your business expenses & ensure you are operating at peak profitability.

- ✓ **Washing and Drying times co ordinated** through highly efficient washing **spin** cycles, which reduces dry times (with less residual water in materials) and aligns washing/drying cycle.
- ✓ Spin: **Super High G-Forge Extraction**, more powerful than the standard 85 G-force, will effectively remove residual water saving up to 40% on water and gas bills.
- ✓ **Intelligent Drive** system offers a calibrated extraction speeds for varying load type.
- ✓ **SoftMount installation** where a poured foundation is not possible. Potential 'out of balance' loads are stabilised through heavy duty coil springs and specialty shock absorbers. A more compact design than competitors, offering more user work space.
- ✓ 39 **Pre-Programmed Settings**, with the option of up to 99 settings. Pre-programs include; overnight soak for stain removal & temperature controlled fills.
- ✓ Solid steel construction. All Welded- No shaky rivets. Skyscraper quality stainless steel casing.

AUSTRALIAN LAUNDRY SYSTEMS (NT) P/L

PH: 08 8948 4100 FAX: 08 8948 4199  
E: admin@alsnt.com.au WEB: alsnt.com.au  
Postal: PO Box 575, Nightcliff. NT. 0814  
Showroom: 39 Delatour Street. Coconut Grove. NT. 0810

Model Dimension and Specifications for the UX Range available through Australian Laundry Systems NT.

Flexible Installation made possible with UX range, Softmount system.

- Full steel construction with stainless steel casing
- Easy access for maintenance and service
- Heavy duty hinge door, with reliable locking mechanism
- Water reuse capable
- Three water inlets standard on models 35-75
- Four water inlets standard on models 100-165
- Bearing protection weap system
- Compact design
- Easy to read ProgressDisplay
- Multi-faceted supply dispenser

Model	UX35	UX55	UX75	UX100	UX135	UX165
Capacity (kg)	15.9	24.9	34.0	45.4	61.2	74.8
Width (mm)	783	900	1060	1200	1200	1300
Depth (mm)	960	1016	1168	1330	1500	1620
Height (mm)	1194	1544	1530	1920	1920	2100
Net weight (kg)	347	570	865	1520	1645	2100
Cylinder diameter	650	750	850	980	980	1095
Cylinder depth	500	530	537	597	775	775
Cylinder volume	167	234	305	451	575	730
Door opening size	300	395	395	500	500	622
Door bottom to floor	395	559	559	648	648	711
Wash speed RPM	10-50	10-50	10-50	10-50	10-50	10-50
Distribution speed RPM	74	69	65	61	61	100
Extraction speed RPM	250-1000	250-1000	250-1000	250-800	250-800	250-750
Extract G-Force	363	418	475	350	350	344
Water inlet conc (mm)	19	19	19	19	19	25
Steam inlet conc (mm)	10	10	10	10	10	19
Drain conc size (mm)	50	75	75	75	75	2 x 75
Motor size HP (kW)	1.5	3	4	5.5	7.5	11.5
Voltage/Hz/phase Circ X	200-240/50-60 1/3 : 15					
Breaker FLA TBA	Tba					
Shipping dimensions (mm)	H	1310	1650	1730	2010	2300
	W	850	1020	1160	1300	1450
	D	1100	1150	1230	1335	1720
Shipping weight (kg)	436	360	995	1697	1822	2319